lease type a plus sign (+) inside this box	_	.1.	ı
lease type a dius sign (+) inside this box	~	1 + 1	ı

PTO/SB/05 (4/98)

Please type a plus sign (+) inside this box

Approved for use through 09/30/2000. OMB 0651-0032

Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

Attorney Docket No.

UTILITY PATENT APPLICATION TRANSMITTAL Only for new nonprovisional applications under 37 C.F.R. § 1.53(b),

First Inventor or Application Identifier

Veksland et al. AUTOMATIC FOCUSING CAMERA WITH MOVING MIRROR BETWEEN FIXED LENS AND FIXED IMAGE SENSOR

Express Mail Label No. EL413096649US

ASI-PT043

Soc			TION ELEMENTS concerning utility patent applicat	tion contents	ADL	DRESS TO	. Box F	Patent Ap	nmissioner for Patents oplication	ro
1. 2.	* F. (Su * Spo (pre - D - C - Si	ee Transi ubmit an on ecification eferred arra escriptive tross Refe tatement	mittal Form <i>(e.g., PTO/SB</i> iginal and a duplicate for fee pro	(/17) occessing) ges 12]		eotide and/o	Computor Amino Inecession Inputer I	ter Prog o Acid Se <i>ary)</i> Readabl y (identio	ram (Appendix) equence Submission e Copy cal to computer copy) g identity of above cop	3 JC564 U.S. P
			d of the Invention			ACCOMPA	ANYING	G APPL	ICATION PARTS	
F	- Brief Summary of the Invention - Brief Description of the Drawings (if filed) - Detailed Description - Claim(s) - Abstract of the Disclosure 3. X Drawing(s) (35 U.S.C. 113) [Total Sheets 2] The state of the Disclosure [Total Sheets 2] The state of								lication, red	
	Co	ontinuation	Divisional Co	ntinuation-in-part (CIP) c	f prior applica				_
une	r CONTINU der Box 4b	JATION or o, is consid	formation: Examiner DIVISIONAL APPS only: The dered a part of the disclosure oration can only be relied upo	of the accompar	nying continua	pplication, fi	sional ap	ch an oat plication	and is hereby incorpora	ated by
			17. CO	ORRESPOND	ENCE ADD	RESS				
	Custom	ner Numbe	r or Bar Code Label (Insert C	Customer No. or At	tach bar code	label here)	or 🕱	Corre	espondence address belo	w
Na	me		olph J. Huis, Esquire							
<u> </u>			and Koenig, P.C.			· · · · · · · · · · · · · · · · · · ·		 		
Aa	ldress		400, One Penn Cente John F. Kennedy Blvd							
Cit	'y	Philac	delphia	State	Р	Ά	Zip C	Code	19103	
Со	untry	U.S.A		Telephone	215	-568-6400)	Fax	215-568-649	9
	Name (F	Print/Type)	Randolph JaH	yis, Esquire	Reg	istration No. ((Attorney/A	gent)	34,626	$\overline{)}$
	Signatur	re	Reide	1///	<u> </u>			Date	February 15, 200	00

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231.

Attorney Docket No. ASI-PT043

TITLE OF THE INVENTION

Automatic Focusing Camera With Moving Mirror Between Fixed Lens And Fixed Image Sensor

BACKGROUND OF THE INVENTION

The present invention is directed to an automatic focusing camera, and more particularly to an automatic focusing line scan camera for use in scanning applications.

In scanning applications, for examples for packages traveling along a conveyor, it is often required that scans be carried out at varying target distances. For example, if a larger package moves along a conveyor beneath a scanner, the distance between the lens of the scanning camera system and the object is shorter than for a smaller package traveling along the same conveyor path. Prior known systems generally provide focusing for the scanning camera by adjusting the position of the lens system or the image sensor to focus the image plane on the senor. However, this can result in higher costs for systems employing movement of one or more lens in order to maintain the optical alignment of the lens relative to one another and the sensor. Additionally, movement of the image sensor can add additional complexity and cost due to the need to provide electrical connections to an from the imaging sensor and to maintain the desired orientation of the sensor over the path of movement.

It would be desirable to be able to provide adjustment of the object focal length without the need for moving either the lens system (or one or more lenses therein) or the sensor relative to one another in order to provide a simple and reliable automatic focusing system for a camera system, preferably for use in scanning applications.

SUMMARY OF THE INVENTION

Briefly stated, the present invention is an automatic focusing camera which includes an image sensor. A fixed lens system is provided having a lens with an object side and an image side. The fixed lens system is located in a fixed position relative to the image sensor. A mirror is moveably positioned between the image side of the lens system and the image sensor. The mirror is located at an angle such that an image observed through the fixed lens system is reflected toward the image sensor. An actuator is connected to the mirror and moves the mirror relative to the lens system to change a distance between the lens system and the image sensor to adjust an object focal length between an object and the camera.

In another aspect, the present invention provides a method for automatic focusing of a camera having an image sensor and a lens system with an objective lens located at a fixed position relative to the image sensor. The method comprises: (a) providing a mirror moveably mounted between an image side of the lens system and the image sensor; and .

(b) adjusting the position of the mirror to vary a length of an optical path between the image sensor and the lens system to vary an object focal point on an object being observed.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

The foregoing summary, as well as the following detailed description of the preferred embodiments of the invention will be better understood when read in conjunction with the appended drawings. For the purposes of illustrating the invention, there is shown in the drawings embodiments which are presently preferred. It should be understood, however, that the invention is not limited to precise arrangements shown. In the drawings:

- Fig. 1 is a plan view of the automatic focusing camera in accordance with the present invention;
- Fig. 2 is a plan view of a second embodiment of an automatic focusing camera in accordance with the present invention;
- Fig. 3 is a plan view of the automatic focusing camera shown in Fig. 2 illustrating the shift in the object focal line as the object focal point moves farther from or nearer to the lens system.

DETAILED DESCRIPTION OF THE INVENTION

Certain terminology is used in the following description for convenience only and is not considered limiting. The words "right", "left", "lower", and "upper" designate directions in the drawings to which reference is made. The terminology includes the words specifically noted above, derivatives thereof and words of similar import. Additionally, the terms "a" and "one" are defined as including one or more of a referenced item unless specifically noted.

Referring to the drawings, wherein like numerals designate like elements throughout, there is shown in Fig. 1 a preferred embodiment of an automatic focusing camera 10 in accordance with the present invention. Preferably, the automatic focusing camera 10 is a line scan camera and includes an image sensor 12 and a fixed lens system 14 having an objective lens 16 with an object side 16a and an image side 16b. The fixed lens system 14 is located in a fixed position relative to the image sensor 12, for example by fixed mounting of the image sensor 12 and the lens system 14 on a common substrate, for example a circuit board. The fixed lens system 14 has an optical axis 22. While the fixed lens system 14 is illustrated as including a single objective lens in the first preferred embodiment of the invention 10, it will be recognized by those skilled in the art from the present disclosure that the fixed lens system 14 may include multiple lenses, depending upon the particular application. However, in accordance with the present invention, it is contemplated that if multiple lens are provided, the lenses would be adjusted to a fixed, in-use position relative to the other lenses as well as the image sensor 12, and that the automatic focusing of the camera 10 would be carried out without further adjustment to the lens system 14.

Still with reference to Fig. 1, a mirror 20 is positioned between the image side 16b of the lens system 14 and the image sensor 12. The mirror 20 is located at an angle such that an image located along the optical axis 22 is observed through the fixed lens system 14 and is reflected toward the image sensor 12. This is illustrated most clearly by the path of the

5

optical axis 22 of the lens system 14 which is reflected by the mirror 20 toward the image sensor 12 generally along a path 32 normal to the face of the image sensor 12.

An actuator 24 is connected to the mirror 20 that moves the mirror 20 relative to the lens system 14 to change a distance between the lens system 14 and the image sensor 12 to adjust an object focal length between an object (not shown in Fig. 1) and the camera 10. As shown in Fig. 1, preferably the mirror 20 is mounted on an arm 28 having a pivot point 30 located along an optical axis 32 of the image sensor 12. The actuator 24 is connected to the mirror 20 via the arm 28. Preferably, the pivot point 30 is located on an opposite side of the image sensor 12 from the mirror 20 and is offset sufficiently such that pivoting movement of the arm 28 approximates linear movement over the range of motion for the mirror 20.

In a preferred embodiment, the actuator 24 is a voice coil. However, those skilled in the art will understand from the present disclosure that the actuator 24 may be constructed as a solenoid or a stepper motor with a lead screw or using any other suitable controllable displacement means. In the first preferred embodiment, the pivot point 30 is formed by a pin connection. However, it will be recognized by those skilled in the art from the present disclosure that the pivot could be provided by a flexible member such as a leaf spring or a living hinge which would provide the additional advantage of biasing the arm 28 in a given direction to maintain greater stability of the mirror 20, if desired.

As shown in Fig. 1, when the actuator 24 is actuated, the arm 28 can be adjusted to a second position, shown in dashed lines as 28', moving the mirror 20 to a second position

5

shown as 20' to adjust the length of the optical path between the lens system 14 and the image sensor 12. This causes the object focal point to vary in a predictable manner as explained in more detail below.

In the preferred embodiment, the focusing mechanism is used in conjunction with a line-scan camera system, such as a line-scan CCD camera as the image sensor 12. This is due to the fact that if the object plane and the nodal plane of the lens system 14 are parallel, then the image plane at the image sensor 12 must also be parallel to both the object and nodal planes in order for a complete image to be in focus. The pivoting of the mirror 20 in the first preferred embodiment causes the sensor plane to be non-parallel to the lens nodal plane resulting in an out-of-focus condition for all except a single line in the sensor plane across the face of the image sensor 12. However, as long the image sensor 12 is a single-line sensor located at this line of perfect focus, then the image sensor 12 will see the object without distortion. This is especially useful for scanning applications where a single scan line is generally being observed and imaged by the camera 10.

Referring now to Fig. 2, a second preferred embodiment of the automatic focusing camera 110 is shown. The second preferred embodiment of the automatic focusing camera 110 is similar to the first embodiment 10 and like elements have been designated with the same reference numerals. The differences between the automatic focusing camera 110 of the second preferred embodiment of the invention and the automatic focusing camera 10 of the first embodiment of the invention are explained in detail below.

5

In the second preferred embodiment of the invention, the automatic focusing camera 110 includes a mirror 120 which is mounted for generally linear movement parallel to the optical axis 22 of the lens system 14. Preferably, the mirror 120 is connected to a linear actuator 124 for movement of the mirror 120 from a first position to a second position 120', as shown by dashed lines in Fig. 2, to change the length of the optical path between the lens system 14 and the image sensor 12. In the second preferred embodiment of the automatic focusing camera 110, since the actuator 124 causes the mirror 120 to move linearly along a path generally parallel to the optical axis 22 of the lens system 14, the object, lens and sensor planes all remain parallel such that the image can be focused on the surface of the image sensor 12. However, the field of view of the image sensor 12 moves orthogonally to the sensor line as shown in Fig. 3. This results in a shift of the object focal line 123 up or down (for example to the position indicated by 123') as the focal point moves farther from or nearer to the lens system 14, respectively. As shown by comparing the first position of the lens 120 in Fig. 2 with the object focal line 123 in Fig. 3 versus the second position of the lens 120' in Fig. 2 and the second object focal line 123' in Fig. 3, this shift becomes apparent.

While in the second preferred embodiment a line-scan camera is also used as the image sensor 12, it is also possible to utilize a two dimensional image sensor 12 in connection with the second preferred embodiment since the object, lens and sensor planes all remain parallel to the field of view of the image sensor 12.

In use, the position of the mirrors 20, 120 of the automatic focusing cameras 10, 110 are adjusted to vary a length of an optical path between the imaging sensor 12 and the lens system 14 to vary an object focal point on an object being observed. In the first preferred embodiment, this is accomplished by moving the mirror about the pivot point 30, shown in Fig. 1, and receiving the image to be scanned on a single line-scan camera, such as a single line CCD camera. In the second preferred embodiment, the mirror 120 is moved linearly along a path parallel to an optical axis 22 of the lens system 14, as shown in Fig. 2, to adjust the position of the mirror 120 in order to focus the object image on the image sensor 12.

While the preferred embodiments of the invention have been described in detail, the invention is not limited to the specific embodiments described above which should be considered as merely exemplary. Further modifications and extensions of the present invention may be developed, and all such modifications are deemed to be within the scope and spirit of the present invention as defined by the appended claims and all legal equivalents thereto.

5

CLAIMS

What is claimed is:

1. Automatic focusing camera comprising:

an image sensor;

a fixed lens system having a lens with an object side and an image side, the fixed lens system being located in a fixed position relative to the image sensor;

a mirror movably positioned between the image side of the lens and the image sensor, the mirror being located at an angle such that an image observed through the fixed lens system is reflected toward the image sensor; and

an actuator connected to the mirror that moves the mirror relative to the lens system to change a distance between the lens system and the image sensor to adjust an object focal length between an object and the camera.

- 2. The automatic focusing camera of claim 1, wherein the mirror is mounted on an arm having a pivot point located along an optical axis of the image sensor and the actuator is connected to the mirror via the arm.
- 3. The automatic focusing camera of claim 2, wherein the pivot point is located on an opposite side of the image sensor from the mirror.

5

- 4. The automatic focusing camera of claim 1, wherein the actuator is a voice coil.
- 5. The automatic focusing camera of claim 1, wherein the mirror is mounted for generally linear movement parallel to an optical axis of the lens system.
- 6. The automatic focusing camera of claim 1, wherein the sensor is a single line sensor.
 - 7. Method for automatic focusing of a camera having an image sensor and a lens system with a lens located at a fixed position relative to the image sensor, comprising:

providing a mirror movably mounted between an image side of the lens system and the image sensor; and

adjusting the position of the mirror to vary a length of an optical path between the imaging sensor and the lens system to vary an object focal point on an object being observed.

- 8. Method for automatic focusing of claim 7, further comprising:
- moving the mirror linearly along a path parallel to an optical axis of the lens system to adjust the position of the mirror.

9. Method for automatic focusing of claim 7, further comprising:

moving the mirror about a pivot point located along an optical axis of the image sensor; and

receiving an image to be scanned as a single line in a plane of the image sensor.

ABSTRACT

An automatic focusing camera which includes an image sensor is provided having a fixed lens system with a lens having an object side and an image side. The fixed lens system is located in a fixed position relative to the image sensor. A mirror is moveably positioned between the image side of at least one lens and the image sensor. The mirror is located at an angle such that an image observed through the fixed lens system is reflected toward the image sensor. An actuator is connected to the mirror and moves the mirror relative to the lens system to change a distance between the lens system and the image sensor to adjust an object focal length between an object and the object side of the lens.





FIG.2






FIG.3

				Express	Mail Labe	el No. EL41	3096649US				
	PTO/SB/01 (12-97) Approved for use through 9/30/00 OMB 0651-0032 Patent and Trademark Office, U S DEPARTMENT OF COMMERCE Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number										
				Attorney Doc	et Number	ASI-PT0	43				
DI	ECLARATION	FOR SIGN	UTILITY OF	First Named I	nventor	Vekslan	Veksland et al.				
	PATENT AF		ATION	C	COMPLETE IF KNOWN						
	(37 CF			Application Nu	Application Number						
(Z)		 .		Filing Date							
	Declaration Submitted OR		mitted after Initia	al Group Art Unit							
	with Initial Filing	(37 (g (surcharge CFR 1.16 (e)) ired)	Examiner Nan	ne						
_											
	As a below named inven	ntor, I her	eby declare that:								
	My residence, post office		·								
	I believe I am the original, names are listed below) o	first and a f the subje	sole inventor (if only ect matter which is c	one name is listed belo laimed and for which a	w) or an origina patent is sought	I, first and joint inve on the invention e	entor (if plural entitled				
	-			ING CAMERA V							
	MIRRO	HBEI	WEEN FIXED	LENS AND FIX	ED IMAGE	SENSOR					
1	the specification of which is attached hereto		(Title	of the Invention)							
	OR was filed on (MM/D			as Un	ited States Appl	ication Number or	PCT International				
	pplication Number			s amended on (MM/DD			(if applicable)				
1	hereby state that I have re	eviewed a	 	•	,	ation, including the	_ ` '' '				
a	mended by any amendme	ent specifi	cally referred to abo	ve							
Ľ	acknowledge the duty to	disclose in	ntormation which is n	naterial to patentability a	as defined in 37	CFR 1.50					
I hereby claim foreign priority benefits under 35 U.S.C. 119(a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT international application which designated at least one country other than the United States of America, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or of any PCT international application having a filing date before that of the application on which priority is claimed.											
Pr	rior Foreign Application Number(s)		Country	Foreign Filing Date (MM/DD/YYYY)	Priority Not Claime		opy Attached? NO				
\vdash											
	Additional foreign applic						ereto.				
H	hereby claim the benefit Application Number			United States provision (MM/DD/YYYY)	iai application(s) listed below					
	Additional provisional application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto.					on a ty data sheet					

[Page 1 of 2]
Burden Hour Statement: This form is estimated to take 0.4 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO Assistant Commissioner for Patents, Washington, DC 20231.

ļ.

State State

Marie South Head

DECLARATION — Utility or Design Patent Application															
I hereby claim the benefit under 35 U S C 120 of any United States application(s), or 365(c) of any PCT international application designating the United States of America, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of 35 U S C. 112, I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application															
U.S	S. Pare	nt Applicati Numb		PCT P	arent				iling Date D/YYYY)			nt Patent N if applicab			
· (manger)															
		CT international													
As a named invand Trademark			ith	Custom OR	er Numb	oer			this application number li	-	•	t all business i Place Custo Number Bar Label he	mer Code		
				liogisto	Regist	ration	Harrio	l giotis					stration		
Name Alfred Stapler Anthony S. Volpe C Frederick Koenig III Randolph J Huis Gerald B Halt, Jr				Number 16,675 28,377 29,662 34,626 37,633				Name Salvatore Anastasi Glenn M Massina Marilou E. Watson Jeffrey M. Glabicki Kao H. Lu				39 40 42 42	mber ,090 ,081 ,213 ,584		
Additional i	registered	practitioner(s)	named c	n supple	emental	Registere	d Prac	titioner	Information sh	eet PTO	/SB/02C	attached here	to		
Direct all corr	•		Custom or Bar (Code L	abel				OR	X C	orrespo	ndence add	ress below		
Name		ndolph J. H oe and Koe													
Address	Sui	te 400, C	ne P	enn	Cent	er									
Address	161	17 John F	. Kei	nned	y Blv	d.				Т	·				
City	Phi	iladelphia	ì				s	tate	PA	ZIP		19103	3		
Country	U.S	S.A.		Те	lephon	ie (2	215)	568	-6400	Fax	(2	15) 568-	5) 568-6499		
believed to be punishable by	true; and fine or in	I statements ma I further that the oprisonment, or issued thereon	iese stat both, u	ements	were m	ade with	the kn	owledae	e that willful ta	alse state	ements a	and the like s	o made are		
Name of So	ole or F	irst Invento	or:					A petit	ion has beer	n filed fo	r this u	nsigned inve	entor		
Gi	iven Nan	ne (first and n		f any])			+		Fami	ly Name					
		Michae	el L.				\perp			Veks	sland				
Inventor's Signature		Mill	My		(ll)	Dela	ló					Date	2-9-00		
Residence: (City	Ma	rlton		State	NJ		Country	, ι	JSA		Citizenship	US		
Post Office A	ddress	204 Bay	/berry	/ Cou	urt										
Post Office A	Address	i													
City		Marlton	State		NJ	ZII	Р	08053 Country U			US	SA			
Additional inventors are being named on thesupplemental Additional Inventor(s) sheet(s) PTO/SB/02A attached hereto															

			$\overline{}$	
Please type a pl	us sign (+) inside	this box ->	+	

PTO/SB/02A (3-97)

Approved for use through 9/30/98 OMB 0651-0032

Patent and Trademark Office, U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a

valid OMB control number

DECLARATION

ADDITIONAL INVENTOR(S) Supplemental Sheet Page <u>1</u> of <u>1</u>

Name of Additional Joint Inventor, if any:									entor			
Given Na	me (first and middle [if any])		Family Name or Surname									
	Richard J.					Skok	owsk	i, Jr.				
Inventor's Signature	Richard	Sh	oli	ns	hi d	7.		Date		-9-00		
Residence: City	Warwick	State	PA	λ	Country	USA		Citizensh	ip	US		
Post Office Address	105 Julian Drive E	ast										
Post Office Address		···						1				
City	Warwick	State	P	A	ZIP	18974	Country	у	US	SA		
Name of Addition	nal Joint Inventor, if an	y:			A petitio	n has been file	d for th	nis unsigne	ed inv	entor		
Given Na	me (first and middle [if any])					Family Na	me or S	Surname				
Inventor's Signature								Date	e			
Residence: City		State			Country		Citizen	Citizenship				
Post Office Address						4						
Post Office Address				·								
City		State			ZIP		Cou	ntry				
Name of Additio	nal Joint Inventor, if an	y:			A petitio	n has been file	ed for th	nis unsıgn	ed inv	rentor		
Given Na	me (first and middle [if any])				Family Na	me or	Surname				
Inventor's Signature	Date											
Residence: City	State					Country				Citizenship		
Post Office Address												
Post Office Address						<u></u>		Т				
City	State ZIP Country											

Burden Hour Statement: This form is estimated to take 0.4 hours to complete Time will vary depending upon the needs of the individual case Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO Assistant Commissioner for Patents, Washington, DC 20231